



**Complies with EN14183**

**Material:**

Steel with EVA handrail foam

Mat: Polyethylene turquoise colour

Leg thickness: 0.9mm

Step size: 300x200mm

Open size: 39x 63x 91cm

Finishing: Powder coating

**Weight:** 4.85kg

Folds to just 6cm wide

**Max. load weight:** 150kg

**Before using the ladder**

1. Always ensure the ladder is fully unfolded and hinges, footplates and safety locking clip are securely in position before use.
2. Do NOT use if damaged in any way.
3. Maximum weight load limit: 150kg.
4. Always take care when mounting and dismounting. Always mount and dismount facing towards the ladder.
5. Always clear the work area of any hazards or obstacles before use, including overhead.
6. Always wear suitable footwear when using the ladder.
7. Do NOT lean from the ladder. Always re-site the ladder to a more suitable position.
8. Only use on a firm, flat and level surface.
9. Periodically check that all nuts and bolts are secure and joints are well lubricated.
10. For domestic use only.
11. Children should be kept away from the work area. Do NOT allow children to climb on the ladder.

**Positioning of the ladder**

- The ladder must be placed in the correct position with rungs or treads level and completely opened until locked.
- Ensure the locking device is engaged before use.
- Use on a flat stable surface.
- Check all electrical equipment in the work area e.g. high-voltage power lines or other exposed electrical equipment.
- The ladder should be placed on its feet, not on the rungs or steps.
- Ladders must not be placed on slippery surfaces (e.g. ice) or soiled surfaces.

**Using the ladder**

- The maximum weight load must not exceed the maximum of 150kg.

- Do not lean over whilst standing on the ladder. Stand inside the stiles and with both feet on the same step / rung.
- Use ladder only for light work of short duration.
- Do not use the ladder outside in adverse weather conditions such as strong winds.
- Do not let children play on the ladder.
- Secure doors (not fire doors) and lock windows in the work area.
- Always face the ladder when climbing and descending.
- When ascending and descending hold on to the handrail.
- Do not use the ladder as bridging.
- Avoid excessive lateral loads, such as when drilling into masonry and concrete.
- Do not stay too long on the ladder. Take regular breaks (tiredness is a risk).
- Equipment carried when climbing a ladder should be light and easy to handle.
- Avoid work that imposes a sideways load on stepladders, e.g. lateral drilling through solid materials (such as brick or concrete).
- When working on a ladder hold on with one hand, if this is not possible, take additional safety precautions.



### Repair

Do not use a damaged ladder. Repairs and maintenance must be performed by a competent person.

### Maintenance

#### Clean the ladder

The ladder can be cleaned with water and a commercial cleaning agent. Colour stains can be removed with turpentine.

ATTENTION: Do not let cleaners drip on the floor.

#### Lubrication of moving parts

All moving parts should be lubricated with commercial oil. In winter, thin oil should be used.

CAUTION: Wipe off excess oil.

### Storage

To fold up the ladder, push the button on the edge of the top rung and push steps up towards the handle.

Protect your ladder from impact of adverse weather. The ladder should be stored horizontally.

During transport to or from the storage area, the head must be fixed and secured from slipping.

### DISPOSAL

- Dispose of all packaging, paper, cartons, plastic and plastic bags in accordance with your local recycling regulations.
- At the end of the product's lifespan please dispose of it at an authorised household waste recycling centre.