

Clear Spray and Seal provides a heavy duty, flexible coating that seals leaks instantly. It is ideal for use on gutters, drain pipes, roofs, waste pipes, window frames etc. It is effective on most surfaces including: concrete, brickwork, roof felt, slate, metal, plastic etc.

DIRECTIONS FOR USE:

1. Only use in open, well ventilated areas. 2. Shake can well (at least two minutes) before use. 3. Spray surfaces from a distance of approximately 40cm (16-18 inches).

For sealing larger leaks, fillers such as mesh or fabric may be used to act as a binder for the Clear Spray and Seal.

Note: May dry with a light-yellow colouring

SAFETY INSTRUCTIONS:

WARNING: Extremely flammable aerosol. Pressurised container; may burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition sources. Do not pierce or burn, even after use. Avoid breathing vapour/spray. Use only outdoors or in a well-ventilated area. When using in an enclosed space, open windows and ensure good circulation of air. For large areas, only spray in the open air and vent the area thoroughly after application. Do not spray into the wind. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Get medical advice/attention if you feel unwell. Dispose of contents/container in accordance with national regulations. Containers should be thoroughly emptied before disposal. Prolonged or repeated contact with skin may cause irritation, redness and dermatitis. In use may form flammable/explosive vapour-air mixture. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Use protective masks or exhaust and ventilating devices. Improper use must be avoided by all means. It is recommended that gloves, goggles and a mask (type 3m - 4251 or equivalent) are used. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do, continue rinsing. If adhesive bonding occurs, do not force eyelids apart. **IF ON SKIN:** Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention if any discomfort continues. This product is not recommended for use by persons suffering from asthma or having any respiratory conditions. Especially in the case of asthma, avoid inhalation or vapour. **IF INHALED:** Remove person to fresh air and keep comfortable for breathing. **IF INGESTED:** Rinse mouth thoroughly with water but **DO NOT INDUCE VOMITING**, seek medical attention immediately and show the container label. Do not pierce or burn, even after use. Take measures against static discharge and avoid release to the environment. Always test on an inconspicuous area prior to use and only proceed when happy with the results. The manufacturer and supplier is not responsible for direct or indirect consequences of the product being delivered, being misused or advice being incorrectly followed.

Contains amongst other ingredients:

ACETONE, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane



DANGER

The Enterprise Department
11 Bridge Street, Bishop's Stortford,
Hertfordshire CM23 2JU



ST14511



CLEAR SPRAY AND SEAL

Heavy duty, flexible coating
seals leaks instantly

SIMPLY SPRAY AND LEAVE

500ml e **650**